

# Alcatel

## SP2502G



### The essentials of business telephony redefined

- **2.8" TFT Color display** for easy access to a variety of business functions through a vivid and intuitive interface
- Access to **large local and network phonebooks** for enhanced contact management
- **Full duplex handsfree** to ease your conference calls
- **Headset and EHS\* support** for convenient conversations in office environments
- Embedded **VPN client for secure remote connections**
- **2 Gigabit** ports



Color display



2 SIP accounts



Ports Gigabit



HD voice



Handsfree

# SP2502G



## MAIN FEATURES

- 2.8", 320x240 TFT color display
- 2 sip accounts
- Power over Ethernet, Gigabit ports
- Full duplex handsfree
- Wideband audio
- RJ9 headset port and headset key
- EHS support for Plantronics headsets (with APD 80)
- Call log: 100 entries (received, dialed, missed)
- Phonebook: local (500 entries, downloadable), XML.
- LDAP, black and white lists
- Caller ID (name & number)
- Multiple built in languages on WUI and phone MMI

## FUNCTION SUPPORT

- Call waiting, call swap, up to 10 call handling
- 2 programmable line/function keys with BLF support
- 4 customizable shortcuts , downloadable wallpaper
- Programmable shortcuts in navigation keys
- Visual indicators (LED or on/ screen:incoming call, MWI, mute, headset, no service)
- Mute, hold, transfer, call forward, call deflection, redial, 3 way conference
- 9 built in melodies
- Do Not Disturb (per line and per phone), keypad lock
- Auto answer (per line)
- Volume control (handset, speakerphone, headset andringers)
- Peer to peer mode, IP Call
- Dial plans, prefix replacement, call barring
- Anonymous call, ACR
- XML browser, action urls , click to talk
- Keypad lock

## IP PBX INTEGRATION

- Voicemail access, MWI
- Network conference
- BLF (list/extension)
- DND&CF sync, SCA
- Intercom, music on hold, multicast paging
- Call park, pickup
- Call completion
- Country call progress tones
- Distinctive ringing
- VIP melodies

## KEYPAD

- 4 customizable softkeys
- Configurable idle mode function for all hardkeys
- 2 programmable line/function keys with BLF support
- 5-way navigation key (configurable shortcuts for idle mode)
- Redial, access to voicemail keys
- Mute, hands free and headset keys
- Volume up and down (on navi keys))

## INTERFACES

- 2 RJ 45 auto sensing 10/100/1000 Mps (LAN/PC)
- 1 RJ 9 port for handset connection
- 1RJ 9 port for headset connection
- 5Vdc power jack

## TECHNICAL SPECIFICATIONS

### VoIP Protocol Support

- SIPv2 (RFC3261)

### Voice Features:

- G722, G711A, G711u, G723.1, G726 32, G729ab
- Wideband audio
- Voice Activity Detection, Comfort Noise Generation,
- Acoustic Echo Cancellation, Packet Loss Concealment,
- Adaptive Jitter Buffer (300ms), AGC , VQR, RTCP XR
- Full duplex handsfree with AEC, 96ms tail length
- DTMF: In band, RFC2833, SIP Info

### Network Features:

- DHCP/Static/PPPoE
- DNS Srv , STUN, NTP
- 802.1x, LLDP
- Port mirroring
- QoS 802.1p/Q, ToS /DSCP

### Security Features:

- TLS, SRTP, HTTPS with mutual certificate authentication
- VPN: L2TP (Basic Unencrypted) / OpenVPN
- Config file AES encryption
- 2 level access privileges (user/admin)
- Password dial, web filter, firewall
- Server and client certificate upload; MAC based device certificate
- Industrial Standard Certifications:
  - FCC, CE

## CONFIGURATION AND MANAGEMENT

### IP address Assignment

- DHCP, static IP, PPPoE

### Configuration Support

- Keypad
- Web browser management (Admin/User), HTTP/HTTPS
- Autoprovision with PnP, HTTP/HTTPS/TFTP/FTP, APRT support , firmware upgrade through provisioning files or notification server
- One click config file generation, config restore
- TR069
- Pcap tracing, syslog

## PHYSICAL & ENVIRONMENTAL

### Mounting

- Adjustable multiposition footstand : 2
- Desk top and wall mountable

### Power over Ethernet

- 802.3af, class 1

### Power Adaptor

- AC100 240V input, 5Vdc/1000mA output (not included, order separately)

### Power Consumption:

- 1.1 1.8W

### Operating temperature:

- From 0° to 40°C

### Operating Humidity:

- 10% to 60% non condensing

### Storage temperature:

- Up to 50°C

### Package dimensions:

- 250x205x70 WxLxH

## COMMERCIAL REFERENCE

### SP2502G

PSU for SP2502 (EU)

PSU for SP2502 (US)

3700601423204

3700601490107

3700601490114